

Brandy's nad Labem																
ZPEVNĚNÝ																
--																
2.92	34.95	50.01	48.89	29.67	50.29	39.06	33.60	45.03	45.00	50.25	30.23	45.07	42.50	42.22	45.00	
J2B11=ŠB.0	ŠB.2	ŠB.3	ŠB.4	ŠB.5	ŠB.6	ŠB.7	ŠB.8	ŠB.9	ŠB.10	ŠB.11	ŠB.12	ŠB.13	ŠB.14	ŠB.15	ŠB	
J2B11=ŠB.1																





The image displays three cross-section diagrams of a road embankment, each showing the profile of the road and the surrounding terrain. The diagrams are labeled with elevation data and slope calculations.

Diagram 1 (Left): Shows a cross-section with a road width of 2.80m. The elevation of the road surface is 195.23m. The elevation of the ground surface is 195.32m. The elevation of the top of the embankment is 198.09m. The elevation of the bottom of the embankment is 194.40m. The elevation of the top of the embankment is 198.09m. The elevation of the bottom of the embankment is 194.40m. The elevation of the top of the embankment is 198.09m. The elevation of the bottom of the embankment is 194.40m.

Diagram 2 (Middle): Shows a cross-section with a road width of 3.05m. The elevation of the road surface is 202.31m. The elevation of the ground surface is 202.46m. The elevation of the top of the embankment is 207.80m. The elevation of the bottom of the embankment is 204.42m. The elevation of the top of the embankment is 207.80m. The elevation of the bottom of the embankment is 204.42m. The elevation of the top of the embankment is 207.80m. The elevation of the bottom of the embankment is 204.42m.

Diagram 3 (Right): Shows a cross-section with a road width of 3.42m. The elevation of the road surface is 210.21m. The elevation of the ground surface is 210.34m. The elevation of the top of the embankment is 210.60m. The elevation of the bottom of the embankment is 207.28m. The elevation of the top of the embankment is 210.60m. The elevation of the bottom of the embankment is 207.28m. The elevation of the top of the embankment is 210.60m. The elevation of the bottom of the embankment is 207.28m.

0.0	0.1	0.2	0.3	0.4	0.5	0.6
0.00 1.31 2.92	0.05 1.70 3.77	0.10 3.40 7.54	0.15 5.10 11.07	0.20 6.80 14.62	0.25 8.50 18.17	0.30 10.20 21.72
0.35 10.65 23.18	0.40 12.35 26.70	0.45 14.05 30.25	0.50 15.75 33.80	0.55 17.45 37.35	0.60 19.15 40.90	0.65 20.85 44.45
0.70 21.40 45.36	0.75 23.10 48.91	0.80 24.80 52.46	0.85 26.50 56.01	0.90 28.20 59.56	0.95 29.90 63.11	1.00 31.60 66.66
1.05 33.30 70.32	1.10 35.00 73.87	1.15 36.70 77.42	1.20 38.40 80.97	1.25 40.10 84.52	1.30 41.80 88.07	1.35 43.50 91.62
1.70 51.65 109.68	1.75 53.35 113.23	1.80 55.05 116.78	1.85 56.75 120.33	1.90 58.45 123.88	1.95 60.15 127.43	2.00 61.85 130.98
2.05 63.55 136.70	2.10 65.25 140.25	2.15 66.95 143.80	2.20 68.65 147.35	2.25 70.35 150.90	2.30 72.05 154.45	2.35 73.75 158.00
2.70 81.50 173.72	2.75 83.20 177.27	2.80 84.90 180.82	2.85 86.60 184.37	2.90 88.30 187.92	2.95 90.00 191.47	3.00 91.70 195.02
3.35 99.45 210.74	3.40 101.15 214.29	3.45 102.85 217.84	3.50 104.55 221.39	3.55 106.25 224.94	3.60 107.95 228.49	3.65 109.65 232.04
4.00 121.40 257.76	4.05 123.10 261.31	4.10 124.80 264.86	4.15 126.50 268.41	4.20 128.20 271.96	4.25 129.90 275.51	4.30 131.60 279.06
4.65 139.35 294.78	4.70 141.05 298.33	4.75 142.75 301.88	4.80 144.45 305.43	4.85 146.15 308.98	4.90 147.85 312.53	4.95 149.55 316.08
5.30 157.30 331.80	5.35 159.00 335.35	5.40 160.70 338.90	5.45 162.40 342.45	5.50 164.10 346.00	5.55 165.80 349.55	5.60 167.50 353.10
6.00 175.25 368.82	6.05 176.95 372.37	6.10 178.65 375.92	6.15 180.35 379.47	6.20 182.05 383.02	6.25 183.75 386.57	6.30 185.45 390.12
6.65 193.20 405.84	6.70 194.90 409.39	6.75 196.60 412.94	6.80 198.30 416.49	6.85 200.00 420.04	6.90 201.70 423.59	6.95 203.40 427.14
7.30 211.15 442.86	7.35 212.85 446.41	7.40 214.55 450.00	7.45 216.25 453.55	7.50 217.95 457.10	7.55 219.65 460.65	7.60 221.35 464.20
7.95 229.10 479.88	8.00 230.80 483.43	8.05 232.50 487.02	8.10 234.20 490.61	8.15 235.90 494.20	8.20 237.60 497.79	8.25 239.30 501.38
8.60 247.05 516.90	8.65 248.75 520.45	8.70 250.45 524.00	8.75 252.15 527.55	8.80 253.85 531.10	8.85 255.55 534.65	8.90 257.25 538.20
9.25 265.00 553.92	9.30 266.70 557.47	9.35 268.40 561.02	9.40 270.10 564.57	9.45 271.80 568.12	9.50 273.50 571.67	9.55 275.20 575.22
10.00 282.95 590.94	10.05 284.65 594.49	10.10 286.35 598.04	10.15 288.05 601.59	10.20 289.75 605.14	10.25 291.45 608.69	10.30 293.15 612.24
10.65 300.90 627.96	10.70 302.60 631.51	10.75 304.30 635.06	10.80 306.00 638.61	10.85 307.70 642.16	10.90 309.40 645.71	10.95 311.10 649.26
11.30 318.85 664.98	11.35 320.55 668.53	11.40 322.25 672.08	11.45 323.95 675.63	11.50 325.65 679.18	11.55 327.35 682.73	11.60 329.05 686.28
11.95 336.80 701.99	12.00 338.50 705.54	12.05 340.20 709.09	12.10 341.90 712.64	12.15 343.60 716.19	12.20 345.30 719.74	12.25 347.00 723.29
12.60 354.75 738.99	12.65 356.45 742.54	12.70 358.15 746.09	12.75 359.85 749.64	12.80 361.55 753.19	12.85 363.25 756.74	12.90 364.95 760.29
13.25 372.70 776.01	13.30 374.40 779.56	13.35 376.10 783.11	13.40 377.80 786.66	13.45 379.50 790.21	13.50 381.20	

	
SUNCAD, s.r.o. náměstí Na Lužinách 3 Praha 13, 155 00	
Datum/Date:	09/2017
Čís. zakázky/Job No.:	96_01_2010
Stupeň/Stage:	PDP5
OU/Local authority:	Brandýs nad Labem - Stará Boleslav
MÚ/ City authority:	Brandýs nad Labem - Stará Boleslav
Objednatel/Client:	Brandýs nad Labem - Stará Boleslav
Akce/Project:	II/610 BRANDÝS NAD LABEM, REKONSTRUKCE KŘÍŽOVATKY PRAŽSKÁ - PRŮMYSLOVÁ A ČÁSTI KOMUNIKACE V UL. PRAŽSKÁ
Profese/Profession:	B - STAVEBNÍ ČÁST B.2 - VODOHOSPODÁŘSKÉ OBJEKTY SO 302 Kanalizace - řad SO 303 Kanalizace - přípojky dešťové SO 304 Kanalizace - přípojky splaškové SO 305 uliční vpusti vč. přípojek
Název/Title:	Podélný profil - Stoka B
Zodp. projektant/Responsible designer:  Ing. Petr Kokeš	
HIP/Project manager:	 Ing. Marek Pejchal
Návrh, vypracování/Elaborated by:	 Ing. Petra Ruthová
Měřítko/Scale:	Souprava/ Copy:
Výkres č./DWG No.:	
B.2.2.5	