



Č. pol.	D [mm]	Délka [m]	Počet ks.	Délka B500B		
				8	10	12
1	8	2.100	10	21.00		
2	10	1.240	10		12.40	
3	10	2.350	8		18.80	
4	10	2.090	3		6.27	
5	10	3.100	8		24.80	
6	10	2.130	14		29.82	
7	10	2.420	9		21.78	
8	12	1.250	41			51.25
9	10	2.170	10		21.70	
10	10	1.930	4		7.72	
11	10	1.200	10		12.00	
12	10	1.130	10		11.30	
13	12	1.230	10			12.30
14	10	1.120	10		11.20	
15	10	1.240	10		12.40	
16	12	5.550	10			55.50
17	12	5.370	10			53.70
18	12	1.460	27			39.42
19	12	1.620	10			16.20
20	12	1.520	10			15.20
21	10	1.720	10		17.20	
22	12	1.220	92			112.24
23	12	1.410	123			173.43
24	8	1.180	11	12.98		
25	8	0.840	3	2.52		
26	12	1.430	6		8.58	
27	12	1.560	2		3.12	
28	8	-x-	21	20.66		
29	12	3.090	2		6.18	
30	12	3.100	3		9.30	
31	12	3.130	2		6.26	
Celková délka				57.16	207.39	562.68
Specifická hmotnost				0.395	0.617	0.888
Hmotnost [kg]				22.6	128.0	499.7
Hmotnost celkem				650.2		



TABULKA VÝZTUŽE				
Položka č. 28 ø8				
Poloha	ks.	Úseky [m]	Délka [m]	Celk. Délka [m]
		X1		
1	1	0.200	0.800	0.800
2	1	0.210	0.820	0.820
3	1	0.220	0.840	0.840
4	2	0.230	0.860	1.720
5	1	0.240	0.880	0.880
6	1	0.250	0.900	0.900
7	1	0.260	0.920	0.920
8	1	0.270	0.940	0.940
9	1	0.280	0.960	0.960
10	1	0.290	0.980	0.980
11	1	0.300	1.000	1.000
12	1	0.310	1.020	1.020
13	1	0.320	1.040	1.040
14	1	0.330	1.060	1.060
15	1	0.340	1.080	1.080
16	1	0.350	1.100	1.100
17	1	0.360	1.120	1.120
18	1	0.370	1.140	1.140
19	1	0.380	1.160	1.160
20	1	0.390	1.180	1.180
Hmotnost celkem [kg]			8.161	

ŘEŠENÁ OBLAST:



BETON

POUŽITÍ:
NAVRŽENO DLE
BETONOVÁ SMĚS:
KRYTÍ:

OCEL

BETONÁŘSKÁ VÝZTUŽ

C25/30 - XC4

ŽB RAMPA
ČSN EN 1992-1-1 Eurokód 2
S4
40 mm - v kontaktu se zemínou
20 mm - v kontaktu se vzduchem

B500 B