

Technical drawing of a bridge cross-section. The drawing shows a symmetrical structure with a central span and side spans. Key dimensions and components are labeled:

- Overall Dimensions:**
 - Top: 800, 3750, 7500, 3750, 800
 - Bottom: 300, 1575, 1100, 1475, 200, 1475, 1100, 1575, 300
 - Total width at base: 8500
- Structural Components and Labels:**
 - PŘEDMĚŘICE** (Gauge) with a downward arrow.
 - BENÁTKY** (Benches) with an upward arrow.
 - ŽÁBRADLNÍ SVODIDLO OROVEN ZADRŽENÍ H2 SÍŤOVÁ VÝPLŇ** (Guardrail with H2 retention and mesh filling).
 - ŽB. ŘÍMSA S LÍCOVÝM PREFABRIKÁTEM** (Concrete curb with precast face).
 - ŘÍMSA KÁTEM** (Curb).
 - PODÉLNÝ SVOD GRP DN200** (Longitudinal GRP drain).
 - NIVELETA** (Leveling point) with a dashed line labeled $OSa II/610$.
 - Dimensions:** 600 (height of curb), 150 (height of guardrail), 85 (height of leveling point), 1350 (height of side span), 1435 (height of central span), 2.5% (slope).

The diagram illustrates the cross-section of a bridge deck with various layers and components labeled:

- PŘEDMĚRICE**: Indicated by a downward arrow pointing to the top surface.
- BENÁTKY**: A central vertical element, likely a support or pier.
- KAMENNÁ DLAŽBA DO BET. LOŽE**: Stone paving over the concrete bed.
- TROJVLADLOVÉ ZÁBRADLÍ Z KOMPOZITU GABIONOVÁ ŽEĐ**: Three-sided composite railing made of gabion mesh.
- VRUBOVÝ KLOUB**: A dovetail joint connecting different sections of the deck.
- SEPARAČNÍ GEOTEXTILIE**: Separation geotextile layer below the main deck structure.
- POLŠTĚR ŠD 0-32 TL. 200-350mm**: A layer of bedding material (sand/gravel) with a thickness of 200-350 mm.

Dimensions and measurements are provided throughout the drawing:

- Overall width: 9481 mm.
- Top edge offsets: 834 mm (left), 7813 mm (center), 833 mm (right).
- Deck width at base: 1203.300 mm.
- Slope ratio: 1:1.5.
- Railing height: 500 mm.
- Bedding layer dimensions: 198.30 mm (width), 500 mm (length), 1000 mm (width), 1500 mm (length).
- Vertical dimensions from bottom: 900 mm, 2191 mm, 1095 mm, 1095 mm, 2191 mm, 600 mm.
- Horizontal dimensions from left: 521 mm, 900 mm, 2191 mm, 1095 mm, 7772 mm, 900 mm, 521 mm.
- Total height from bottom: 8500 mm.

(DLE TKP18)

C25/30	XA1		
C12/15	X0		
C12/15	X0		
C30/37	XA1	XF3	
C35/45	XF4	XD3	XC4
C30/37	XF1		
C30/37	XF2	XD1	XC2
C35/45	XF2	XD1	XC2
C25/30	XF2		
C30/37	XF4	XD3	XC4
C30/37	XF4	XD3	XC4
C30/37	XF4	XD3	XC4
C20/25n	XF3		
C25/30	XF3		
C8/10			
C35/45	XF4		

(DLE ČSN 42 0139)

(DLE ČSN P 74 2871)

ČÁST B

PONTEx S.R.O.®
Praha 4, Bezová 1658, 147 14
tel: +420 244062215 fax: +420 244461038
e-mail: pontex@pontex.cz

Kraj:	Středočeský
Datum	Stupeň
05/2018	PDPS
Souprava	Č. přílohy
	3